

IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~striketrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please CANCEL claims 3 and 11 without prejudice or disclaimer and AMEND claims 1, 4, 5, 10, 12, 18, 21, and 22 in accordance with the following:

1. (CURRENTLY AMENDED) An optical pickup actuator for driving, via a magnetic driving unit, in focusing, tracking, and tilting directions, a bobbin on which an objective lens is disposed, comprising

at least one damping member disposed at a position where great changes in the optical pickup actuator occur when the magnetic driving unit drives the bobbin in one of the focusing, tracking, and tilting directions, so that a size of a second resonant peak is reduced,

wherein the magnetic driving unit includes:

first magnets disposed at opposing sides of the bobbin, respectively;

tracking coils which are wound around the bobbin to oppose respective ones of the first magnets;

second magnets which are spacedly disposed from respective ones of the first magnets, respectively; and

focusing coils which are wound between the first magnets and the second magnets, and wherein a first damping member is inserted within an entire center portion of the focusing coils and surrounded thereby,

wherein the bobbin has corners and second damping members are respectively disposed at each corner.

2. (CANCELED)

3. (CANCELLED)

4. (CURRENTLY AMENDED) The optical pickup actuator of claim-~~3~~1, wherein a metallic heterogeneous material is mixed with the second damping member.

5. (CURRENTLY AMENDED) The optical pickup actuator of claim-31, wherein a metallic heterogeneous material is mixed with the first damping member.

6. (ORIGINAL) The optical pickup actuator of claim 1, wherein the bobbin has corners and at least one of the at least one damping member is disposed at each corner.

7. (ORIGINAL) The optical pickup actuator of claim 1, wherein a metallic heterogeneous material is mixed with the at least one damping member.

8. (ORIGINAL) The optical pickup of claim 1, wherein the bobbin is movably supported by plural suspension wires.

9. (PREVIOUSLY PRESENTED) The optical pickup actuator of claim 1, further comprising:

first yokes to which the first magnets are respectively attached;

second yokes to which the second magnets are respectively attached; and

third yokes to which third magnets are respectively attached.

10. (CURRENTLY AMENDED) An optical pickup actuator comprising:

a base;

a moving unit in which an objective lens is disposed at a side thereof and having a receiving hole at a center thereof;

~~a-damping members~~ inserted above and below~~in~~ shoulder portions of both sides of the receiving hole near the objective lens so that a size of a second resonant peak is reduced;

a bobbin which is receivable in the receiving hall so as to move together with the moving unit; and

a magnetic driving unit disposed in the base and which drives the moving unit in focusing, tracking, and tilting directions,

wherein the magnetic driving unit includes:

focusing coils which are wound around the bobbin;

tracking coils which are wound around a side of the bobbin and are disposed at the center portion of the receiving hall; and

first and second magnets disposed at sides of the tracking coils.

11. (CANCELLED)

12. (CURRENTLY AMENDED) The optical pickup actuator of claim ~~11~~ 10, wherein a metallic heterogeneous material is mixed with the damping member.

13. (ORIGINAL) The optical pickup actuator of claim 10, wherein a metallic heterogeneous material is mixed with the damping member.

14. (PREVIOUSLY PRESENTED) The optical pickup of claim 10, wherein the bobbin is movably supported by plural suspension wires.

15. (ORIGINAL) The optical pickup apparatus of claim 14, wherein the receiving hall has shoulders at opposing sides thereof, and wherein the at least one location where changes of the actuator occur most frequently are the shoulders.

16. (ORIGINAL) The optical pickup of claim 14, further comprising:
a first yoke to which the first magnet is attached; and
a second yoke to which the second magnet is attached.

17. (PREVIOUSLY PRESENTED) The optical pickup of claim 16, wherein the bobbin includes a first guide hole, the receiving hall includes a second guide hole, and the first and second yokes are respectively received by the first and second guide holes.

18. (CURRENTLY AMENDED) A method of reducing a frequency of a second resonance peak of an optical pickup, comprising

inserting at least one damping member in at least one location of the optical pickup where great change occurs during tracking, the at least one location being an entire center of the focusing coils of the optical pickup so that the at least one damping member is surrounded by the focusing coils or in each corner of the bobbin of the optical pickup;

damping vibration of the optical pickup during tracking at the at least one location where the great change occurs during the tracking, via the at least one damping member,

wherein the damping includes at least one of damping vibration at a center of focusing coils of the optical pickup and damping the vibration at corners of a bobbin of the optical pickup.

19. (CANCELLED)

20. (CANCELLED)

21. (CURRENTLY AMENDED) The method of claim 2018, wherein the damping member is mixed with a metallic heterogeneous material.

22. (CURRENTLY AMENDED) A method of increasing a gain margin of an optical pickup, comprising reducing a frequency of a second resonance peak of an optical pickup by damping vibration of the optical pickup during tracking at least one location where great change occurs during the tracking, by damping vibration at a center of focusing coils of the optical pickup by inserting at least one damping member in the entire center of the focusing coils so that the at least one damping member is surrounded by the focusing coils or damping vibration at corners of a bobbin of the optical pickup by inserting at least one damping member in each corner of the bobbin.

23. (CANCELLED)

24. (CANCELLED)

25. (PREVIOUSLY PRESENTED) The method of claim 22, wherein the damping member is mixed with a metallic heterogeneous material.